

Care 800 Cleanflush™

Sanitary Facilities - Access and Mobility 4.5/3 litre Vitreous China Wall Faced Close Coupled Toilet Suite



The 4.5/3 dual flush **Care 800 Cleanflush™** wall faced close coupled toilet suite is designed to provide a raised seat height of between 460 – 480mm for accessible applications. With a pan projection of 800mm ±10mm, compliance to AS 1428.1-2009 Amd. 1 for wheelchair access can be easily achieved. The pan connection system includes the patented Caroma Uni-Orbital® connector that extends to any position in a 50mm radius, unlike traditional connectors that only move backwards and forwards. The setout range is from 140mm – 335mm with a recommended setout of 190mm.

Featuring rimless pan technology, the **Care 800 Cleanflush™** is a superior flushing system suitable for commercial and domestic applications. Incorporating several patented technologies, the Caroma Flow Splitter™ evenly flows water around the top of the bowl to meet at the Caroma Flow Balancer™ which directs the water powerfully into the sump. The Caroma Cleanflush™ pan is easy to clean, provides full visibility of any grime build up and provides a cleaner clean with every flush for peace of mind.

Important : Reference must be made to AS 1428.1-2009 with current amendments to determine circulation space, grab rail and installation requirements. The dimensions in this sheet may change with amendments to the standard.

Pan: Care 800 Cleanflush™ close coupled 4.5 litre full flush wash down rimless type.

Traps: Universal trap.

Cisterns: Care 800 cistern – has a free fitting lid and is suitable for domestic and light commercial applications. Available as internal overflow. Standard back inlet.

Vandal Resistant Conversion Kit – A simple to install conversion is available for the standard mechanism to lock lid onto the cistern, recommended for use in heavy use commercial areas. Code No.750109. Cistern inlet stop valve and inlet connection is concealed within the cistern and is included. **Important: Working pressure minimum 30kPa to maximum 1000kPa flow pressure. Rain water tank compliant. Accurate wall setout for B.S.P. 1/2" Nipple water inlet connection is essential.**

Buttons: Round Care Button - Metal (supplied). Other button options sold separately. See section 16 - CARE BUTTONS for further details.

Seats: Pedigree II Care single flap, Colani single flap and Caravelle Care single flap seats available in Caroma White (W), Sorrento Blue (SB) and Anthracite Grey (AG). See Section 15 - SEATS for further details. Reference to AS1428.1-2009 must be made in regards to luminance contrast when selecting the seat colour.

Colour: White only.

Installation: The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.

Dimensions: All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

